

<b>Load capacity</b>	<b>Q(kg)</b>	<b>1500</b>
Load centre distance	c(mm)	600
Fork height,lowered	$h_{13}$ (mm)	85 / 75
Tyre size,front	mm	Φ195x70
Tyre size,rear (single)	mm	Φ80x93 / Φ74x93
Tyre size,rear (double)	mm	Φ80x70 / Φ74x70
Wheels, number front rear (x = driven wheels)		1x2(4)
Max. lift height	$h_3$ (mm)	190/180
Height of tiller in drive position min./max	$h_{14}$ (mm)	700/1250
Overall length	$l_1$ (mm)	1654/1724
Length to face of forks	$l_2$ (mm)	504
Overall width	$b_1$ (mm)	685/562
Fork dimensions	s/e/l(mm)	53/160/1150(1220)
Width overall forks	$b_3$ (mm)	520/550/685
Aisle width for pallets 1000x1200(1200crossways)	$A_3$ (mm)	2260/2328
Aisle width for pallets 800x1200(1200lengthways)	$A_4$ (mm)	2128/2365
Turning radius	$W_a$ (mm)	1454/1424
Travel speed, lader/unladen	Km/h	4.3/4.8
Battery voltage/nominal capacity K20	V/Ah	24/65
Battery dimensions l/w/h	mm	228/138/214
Battery weight	Kg	36
Service weight(with battery)	Kg	205

